

Jeep®

SAFETY FOOTWEAR

HAWK TOE MH

EN ISO 20345:2022+A1:2024

S3S CI HI LG SR FO SC HRO

Size : 40/47

REF. – YM5100SN

Color 020 Military

750 gr (weight per shoe)

NORMS

- (A) Antistatic footwear
- (E) Energy absorption at the heel
- (SR) Slip resistance (ceramic surface covered with glycerine)
- (PS) Resistance to perforation (non-metallic insert, PS type)
- (LG) Footwear suitable for ladder grip
- (CI) Insulation against cold at outsole level
- (HI) Insulation against heat at outsole level
- (FO) Outsole resistant to hydrocarbons
- (HRO) Resistance of the outsole to contact heat

UPPER

Upper: full-grain leather
Lining: breathable mesh
Fastening: lacing
Toe cap: fiberglass toe cap

OUTSOLE Jeep Outdoor

Injected PU/Rubber outsole, PU midsole and rubber wear outsole
Standard anti-perforation outsole “PS” compliant with EN ISO 22568-4:2021
Ultra Soft memory PU insole
Slip resistance “SR” compliant with EN ISO 20345:2022

AREAS OF USE

General use / Logistics / Building and construction / Transport / Maintenance / Industry / Agriculture / Oil and gas / Mining / Heavy industry




PLUS

Nylon and micro-suede upper
Fiberglass toe cap, lightweight and athermic, 200 J impact resistance
15 kN compression resistance
Textile anti-perforation outsole type “PS”

100% non-magnetic boot

Shock-absorbing, hydrophilic, Ultra Soft insole, compliant with “CI” requirements

JEEP Outdoor rubber outer outsole providing HRO resistance and SR slip resistance in accordance with EN ISO 20344:2021



Jeep®

SAFETY FOOTWEAR
Designed in Italy

Creativity - Innovation - Technology - Service

BI&DO Srl – Via Panà 56 bis – 35027 Noventa Padovana- Italy ph.: +39
049 8700006 - info@biedo.biz – jeep-footwear.com/safety

Jeep®

SAFETY FOOTWEAR

HAWK TOE MH

EN ISO 20345:2022+A1:2024

S3S CI HI LG SR FO SC HRO

Size : 40/47

REF. – YM5100SN

Color 030 Dk.Brown

750 gr (weight per shoe)

NORMS

- (A) Antistatic footwear
- (E) Energy absorption at the heel
- (SR) Slip resistance (ceramic surface covered with glycerine)
- (PS) Resistance to perforation (non-metallic insert, PS type)
- (LG) Footwear suitable for ladder grip
- (CI) Insulation against cold at outsole level
- (HI) Insulation against heat at outsole level
- (FO) Outsole resistant to hydrocarbons
- (HRO) Resistance of the outsole to contact heat

UPPER

Upper: full-grain leather
Lining: breathable mesh
Fastening: lacing
Toe cap: fiberglass toe cap

OUTSOLE Jeep Outdoor

Injected PU/Rubber outsole, PU midsole and rubber wear outsole
Standard anti-perforation outsole “PS” compliant with EN ISO 22568-4:2021
Ultra Soft memory PU insole
Slip resistance “SR” compliant with EN ISO 20345:2022

AREAS OF USE

General use / Logistics / Building and construction / Transport / Maintenance / Industry / Agriculture / Oil and gas / Mining / Heavy industry




PLUS

Nylon and micro-suede upper
Fiberglass toe cap, lightweight and athermic, 200 J impact resistance
15 kN compression resistance
Textile anti-perforation outsole type “PS”

100% non-magnetic boot

Shock-absorbing, hydrophilic, Ultra Soft insole, compliant with “CI” requirements

JEEP Outdoor rubber outer outsole providing HRO resistance and SR slip resistance in accordance with EN ISO 20344:2021



Jeep®

SAFETY FOOTWEAR
Designed in Italy

Creativity - Innovation - Technology - Service

BI&DO Srl – Via Panà 56 bis – 35027 Noventa Padovana- Italy ph.: +39
049 8700006 - info@biedo.biz – jeep-footwear.com/safety

Jeep®

SAFETY FOOTWEAR

HAWK TOE MH

EN ISO 20345:2022+A1:2024

S3S CI HI LG SR FO SC HRO

Size : 40/47

REF. – YM5100SN

Color 062 Black

750 gr (weight per shoe)

NORMS

- (A) Antistatic footwear
- (E) Energy absorption at the heel
- (SR) Slip resistance (ceramic surface covered with glycerine)
- (PS) Resistance to perforation (non-metallic insert, PS type)
- (LG) Footwear suitable for ladder grip
- (CI) Insulation against cold at outsole level
- (HI) Insulation against heat at outsole level
- (FO) Outsole resistant to hydrocarbons
- (HRO) Resistance of the outsole to contact heat

UPPER

Upper: full-grain leather
Lining: breathable mesh
Fastening: lacing
Toe cap: fiberglass toe cap

OUTSOLE Jeep Outdoor

Injected PU/Rubber outsole, PU midsole and rubber wear outsole
Standard anti-perforation outsole “PS” compliant with EN ISO 22568-4:2021
Ultra Soft memory PU insole
Slip resistance “SR” compliant with EN ISO 20345:2022

AREAS OF USE

General use / Logistics / Building and construction / Transport / Maintenance / Industry / Agriculture / Oil and gas / Mining / Heavy industry




PLUS

Nylon and micro-suede upper
Fiberglass toe cap, lightweight and athermic, 200 J impact resistance
15 kN compression resistance
Textile anti-perforation outsole type “PS”

100% non-magnetic boot

Shock-absorbing, hydrophilic, Ultra Soft insole, compliant with “CI” requirements

JEEP Outdoor rubber outer outsole providing HRO resistance and SR slip resistance in accordance with EN ISO 20344:2021



Jeep®

SAFETY FOOTWEAR
Designed in Italy

Creativity - Innovation - Technology - Service

BI&DO Srl – Via Panà 56 bis – 35027 Noventa Padovana - Italy ph.: +39
049 8700006 - info@biedo.biz – jeep-footwear.com/safety