


Jeep



Outdoor

HAWK BOOT

EN ISO 20345:2022+A1:2024 S7S CI HI LG SR FO HRO

Sizes: 40/47

COD.: YM5120SN

750 g (weight of each boot)

NORMS

EN ISO 20345:2024 S7S CI HI LG SR FO HRO

- (A) Antistatic footwear
- (E) Energy absorption at the heel
- (SR) Slip resistance (ceramic surface coated with glycerine)
- (PS) Penetration resistance (non-metal insert, PS type)
- (WR) Water resistance of entire shoe
- (LG) Ladder grab footwear
- (CI) Insulation against the cold at the sole
- (HI) Insulation against the heat at the sole
- (FO) Fuel oil-resistant outsole
- (HRO) Outsole resistance to hot contact

UPPER

Upper : Full grain leather
Lining : Mesh breathable
Fastening : Laces
Toe-cup : Fiberglass

SOLE Jeep Outdoor

Injector sole PU/Rubber, PU midsole and Rubber outsole
Anti puncture insole "PS" standard according to EN ISO 22568-4:2021 standard
Insock Ultra Soft PU memory
Slip resistance "SR" according to EN ISO 20345:2022

ENVIRONMENTS

General Purpose/ Logistic / Building Construction / Transport /
Maintenance / Industry / Agriculture /
Oil and Gas / Mines / Heavy Industry



PLUS

Nylon/Microsuede upper
Fiberglass toe-cap light and athermal, impact resistance 200 J, 16, 0 mm (norme ≥ 14)
Compression resistance at 15 k N, 20, 0 mm (norme ≥ 14). Textile anti-puncture insole type "PS".
Boot 100% non-magnetic.



Cushioning, hydrophilic, Ultra Soft Insock, conform to "CI" standards

JEEP Outdoor rubber outsole for HRO resistance and SR slip resistance according to EN ISO 20344:2021 standards:

- A- Coefficient of friction forward heel : 0,32 (norme $\geq 0,31$)
- B- Coefficient of friction backward forepart : 0,40 (norme $\geq 0,36$)
- C- Coefficient of friction forward heel : 0,34 (norme $\geq 0,19$)
- D- Coefficient of friction backward forepart : 0,25 (norme $\geq 0,22$)



Jeep

SAFETY FOOTWEAR
Designed and produced in Italy

Creativity - Innovation - Technology - Service

BI&DO Srl - Via Panà 56 bis - 35027 Noventa Padovana- Italy

ph.: +39 049 8700006 - info@biedo.biz - jeep-footwear.com/safety