


# Jeep



**Outdoor**

## HAWK TATTING

**EN ISO 20345:2022+A1:2024 S7S CI HI LG SR FO HRO**

**Sizes: 40/47**

**COD.: YM5130SN**

**750 g ( weight of each boot )**

### NORMS

EN ISO 20345:2024 S7S CI HI LG SR FO HRO

- (A) Antistatic footwear
- (E) Energy absorption at the heel
- (SR) Slip resistance (ceramic surface coated with glycerine)
- (PS) Penetration resistance (non-metal insert, PS type)
- (WR) Water resistance of entire shoe
- (LG) Ladder grab footwear
- (CI) Insulation against the cold at the sole
- (HI) Insulation against the heat at the sole
- (FO) Fuel oil-resistant outsole
- (HRO) Outsole resistance to hot contact

### UPPER

Upper : Nylon/Microsuede  
Lining : Mesh breathable  
Fastening : Jeep Rotor  
Toe-cup : Fiberglass

### SOLE Jeep Outdoor

Injector sole PU/Rubber, PU midsole and Rubber outsole  
Anti puncture insole "PS" standard according to EN ISO 22568-4:2021 standard  
Insock Ultra Soft PU memory  
Slip resistance "SR" according to EN ISO 20345:2022

### ENVIRONMENTS

General Purpose / Logistic / Building Construction / Transport /  
Maintenance / Industry / Agriculture /  
Oil and Gas / Mines / Heavy Industry



### PLUS


Nylon/Microsuede upper  
Fiberglass toe-cap light and athermal, impact resistance 200 J, 16, 0 mm ( norme  $\geq 14$  )  
Compression resistance at 15 k N, 20, 0 mm ( norme  $\geq 14$  ). Textile anti-puncture insole type "PS".  
Boot 100% non-magnetic.



Cushioning, hydrophilic, Ultra Soft Insock, conform to "CI" standards

JEEP Outdoor rubber outsole for HRO resistance and SR slip resistance according to EN ISO 20344:2021 standards:

- A- Coefficient of friction forward heel : 0,32 (norme  $\geq 0,31$ )
- B- Coefficient of friction backward forepart : 0,40 (norme  $\geq 0,36$ )
- C- Coefficient of friction forward heel : 0,34 (norme  $\geq 0,19$ )
- D- Coefficient of friction backward forepart : 0,25 (norme  $\geq 0,22$ )



# Jeep

**SAFETY FOOTWEAR**  
Designed and produced in Italy

**Creativity - Innovation - Technology - Service**

BI&DO Srl - Via Panà 56 bis - 35027 Noventa Padovana- Italy

ph.: +39 049 8700006 - info@biedo.biz - jeep-footwear.com/safety