

## ENDURE TRACKED ML

EN ISO 20345:2022+A1:2024 S7S FO SR ESD

Size : 40 / 47

REF. YM6110SS

Color 020 Military

660 gr ( weight per shoe)

### NORMS

EN ISO 20345:2022+A1:2024 S7S FO SR ESD

(A) Antistatic footwear

(E) Energy absorption in the heel

(SR) Slip resistance (ceramic tile floor with glycerine)

(PS) Penetration resistance (non-metallic insert, type PS)

(WR) Water penetration and absorption resistance of the entire footwear

(FO) Outsole resistant to hydrocarbons

ESD Electrostatic dissipative footwear compliant with EN IEC 61340-5-1:2024

### UPPER

Technical polyester mesh with TPU reinforcements

Breathable mesh lining with waterproof membrane

Fiberglass protective toe cap (COMPOSITE)

### JEEP Indoor OUTSOLE

Midsole EVA Extrabound

Outsole in hydrocarbon-resistant rubber (FO)

Anti-perforation outsole standard PS compliant with EN ISO 22568-4:2021

PU Ultra Soft memory foam insole

Slip resistance SR compliant with EN ISO 20345:2022+A1:2024

### AREAS OF USE

General use / Logistics / Handling / Transport / Maintenance / Light industry / Airport / Indoor services



### PLUS

Fiberglass protective toe cap

Lightweight and athermal

Impact resistance 200 J

Residual deformation ≤ 16.0 mm

Compression resistance 15 kN

Residual deformation ≤ 20.0 mm

Textile anti-perforation outsole type PS

100% non-magnetic boot.

